

Connectors



RJ-12 (for display)



RS-232 (for printer)



Specification

Product	Thermal Printer P30	
Display	Dimension	2.8inch TFT screen
	Displaying Currency, Piece, Value when the coin machine works.	
Printing	Printing method	Thermal line
	Resolution	203Dpi(8dot/mm)
	Printing speed	60-80mm/s
	Effective Printing width	48mm
	Interface	Printer: RS232 / Display: RJ-12
Paper	Serial port configuration	Baud rate:9600 data bits: 8 parity: no
	Paper type	Thermal
	Paper wide	57.5±0.5mm
	Paper diameter	Max.40mm
	Paper thickness	0.05-0.09mm
Reliability	Paper loading method	Easy Loading
	Print head life	50km
	Typeface	Chinese
Bar Code	English	GBK:16*16,24*24
	one-dimesional	ASCII:8*16,9*17,9*24,12*24
	two-dimesional	UPC-A,UPC-E,EAN8,EAN13,code39, IIF,CODEBAR,CODE128,CODE9
Memory	RAM	20K
	Flash	256K
	Power Supply	DC5V2A, Instantaneous peak current 3A
Software	Instruction Set	ESC/POS
	Drive	Windows XP, 7, 8, 10/Linux
	SDK	Windows SDK/Linus SDK/Android SDK
Environment	Working temperature	-10°C -50°C
	Working humidity	20%RH-85%RH
	Savings temperature	-20°C-60°C
	Savings humidity	5%-90%RH
	Dimention	148*108*82mm



SOLID BUSINESS MACHINES CENTER, INC.

SUITE 303, SINGSON BUILDING, PLAZA MORAGA, BINONDO, MANILA, PHILIPPINES 1006
 Trunkline : (632) 8242-1111 Connecting all Departments Fax No.: (632) 8242-1345, 8242-1348
 e-mail : sales@solidmac.com.ph

www.solidmac.com.ph